MEJ PRODUCT TECHNICAL DATA SHEET



ARTICLE: 1007BL | 1007AL

DESCRIPTION: POLYETHYLENE LONG STRIP
POLYETHYLENE SPLASHBACK

FEATURES:

MATERIAL: EXTRUDED PEHD300

COMPOSITION: COPOLYMER OF ETHYLENE - 1 - HEXENO WITH ADDITIVES

HARDNESS: PE300 (HIGH DENSITY) = 62 SHORE D ELASTICITY POINT: PE300 (HIGH DENSITY) = 527 MPA MELTING POINT: PE300 (HIGH DENSITY) = 130/135°C

SCREWS: IN STAINLESS STEEL MM 4X30

COMPLIANCE:

IN COMPLIANCE WITH THE REGULATIONS:

·REG. (CE) N.° 2023/2006 ·REG. (CE) N.° 1935/2004 ·REG. (CE) N.° 178/2002 ·REG. (CE) N.° 852/2004

INFORMATION ABOUT SPECIFIC MIGRATIONS:

WE GUARANTEE THAT MANUFACTURING OPERATIONS ARE CARRIED OUT IN COMPLIANCE WITH GMP STANDARDS AND THAT THE SUBSTANCES WE USE COMPLY WITH REGULATIONS, IN ACCORDANCE WITH OUR INTERNAL SUPPLIER QUALIFICATION PROCEDURE.

STANDARD SIZES IN CM:

(TOLERANCE +/- 0,5 CM)

LONG STRIP STANDARD SIZES

LENGTH: SAME AS CUTTING BOARD LENGTH

WIDTH: 2 CM THICKNESS: 2 CM

SCREWED UNDER THE CUTTING BOARD WITH STAINLESS STEEL SCREWS OR

SUPPLIED WITH HOLES AND SCREWS TO BE ASSEMBLED

SPLASHBACK STANDARD SIZES

LENGTH: SAME AS CUTTING BOARD LENGTH


WIDTH: 5 CM THICKNESS: 2 CM

SCREWED ON THE TOP OF THE CUTTING BOARD WITH STAINLESS STEEL SCREWS OR

SUPPLIED WITH HOLES AND SCREWS TO BE ASSEMBLED

FOR CUSTOMISED SIZES PLEASE CONTACT US AT THE FOLLOWING E-MAIL ADDRESS : SALES@MEJ-CEPPOFRUTTERO.COM

AVAILABLE COLOURS:





FOR INSTRUCTIONS USE AND MAINTENANCE, PLEASE REFER TO THE DEDICATED PAGE AT THE FOLLOWING LINK: HTTPS://MEJ-CEPPOFRUTTERO.COM/MAINTENANCE/

NOTE: OUR COMPANY IS CONSTANTLY ENGAGED IN A PROGRAMME AIMED AT IMPROVING OUR PRODUCTS, THEREFORE WE RESERVE THE RIGHT TO CHANGE SOME SPECIFICATIONS WITHOUT PRIOR NOTICE.